

APPARATUS AND METHOD FOR WEIGHING MAILPIECES IN MOTION

FIELD OF THE INVENTION

The invention disclosed herein relates generally to automated mail sorting and more particularly, an apparatus and method for weighing mail in motion, or on the fly, while
5 maintaining the mail in a vertical orientation.

BACKGROUND

The processing and handling of mailpieces consumes an enormous amount of human and financial resources, particularly if done manually. In addition to the postal service, the processing and handling of mailpieces occurs at each and every business or site where
10 communication via the mail delivery system is utilized. Various pieces of mail generated by multiple departments and individuals within a company need to be collected, sorted, addressed and franked as part of the outgoing mail process. Additionally, incoming mail needs to be collected and sorted efficiently to ensure that it gets to the addressee in a minimal amount of time. Since much of the mail being conveyed through the mail system is critical in nature, it is
15 imperative that the processing and handling of both the incoming and outgoing mailpieces be efficient and reliable so as not to impact negatively the operation of the business.

In view of the above, various automated mail handling machines have been developed for processing mail (removing individual pieces of mail from a stack and performing subsequent actions on each individual piece of mail). However, in order for these automatic mailing
20 machines to be effective, they must process and handle "mixed mail." The term "mixed mail" is used herein to mean sets of intermixed mailpieces of varying size (postcards to 9" by 12" flats), thickness, and weight. In addition, the term "mixed mail" also includes stepped mail (i.e., an envelope containing an insert which is smaller than the envelope to create a step in the envelope), tabbed and untabbed mail products, and mailpieces made from different substrates.
25 Thus, the range of types and sizes of mailpieces which must be processed is extremely broad

and often requires trade-offs to be made in the design of mixed mail feeding devices in order to permit effective and reliable processing of a wide variety of mixed mailpieces.

In known mixed mail handling machines which separate and transport individual pieces of mail away from a stack of mixed mail, the stack of mixed mail is first loaded onto some type of transport system for subsequent sorting into individual pieces of mail. Typically, it is preferable to transport a mailpiece in a vertical orientation (on its bottom edge) in order to facilitate the manipulation of individual mailpieces. In systems handling outgoing mail, it is necessary to affix the individual mailpieces with the proper postage. To calculate proper postage it is necessary for the system to determine the distance and manner in which a mailpiece is being sent in addition to its size and weight.

Various scanning and sorting technologies have been implemented as part of automated mail handling systems to determine the distance and manner in which a mailpiece is being sent along with its size. However, prior art systems of mail handling do not adequately provide for the accurate calculation of the weight of a particular mailpiece as it is being processed. To weigh a mailpiece as quickly and accurately as possible, it is desirable to minimize the amount of vibration while weighing the mailpiece. The method used in numerous contemporary systems is to stop the transport of the mailpiece during weighing. While this reduces the vibration caused by the transport, it also increases the cycle time of the mailpiece due to the time required to decelerate the mailpiece, wait for the transport to settle, measure the weight of the mailpiece and accelerate the mailpiece out of the system. Still other contemporary mail handling systems require that the weighing process be performed on a horizontally oriented mailpiece.

Although weighing mailpieces while in transport reduces the need for stopping the system, certain situations require the mail process to be halted. For example, if the weight of the mailpiece is very close to the postal weight break, the accuracy needed to prevent an inaccurate weight classification may require more time and scale stability than can be provided

a moving transport. In such a case, there are three choices: 1) apply postage that may be incorrect, 2) acknowledge the incorrectly weighed mailpiece and divert it away from the stack of mail, or 3) stop the transport and wait for the scale to stabilize and then reweigh the mailpiece. The present invention provides for the third scenario, i.e., stop-on-demand weighing. For example, first class letter rates increase by the ounce. Thus, the postal weight breaks are at one ounce, two ounces, three ounces and so forth. When the system weighs a mailpiece, if the postal weight break is within the weight of the mailpiece plus or minus the weighing system's margin of error, the mailpiece is reweighed. This feature allows the system to automatically stop when more precise measurements are needed.

One of the problems of the prior art is that an apparatus is not available for the accurate calculation of the weight of a mailpiece while the mailpiece is in a vertical orientation, that is, on a mailpiece's bottom edge. Another problem of the prior art is that mechanical vibrations introduced by the system generate inaccurate weight measurements. Yet another problem of the prior art is that the weighing process requires the re-orientation of the mailpiece to be weighed or a stoppage in the mail handling process in order to generate an accurate weight measurement. Therefore, a method is needed to provide for the efficient measurement of the weight of a mailpiece while maintaining the vertical orientation of the mailpiece.

SUMMARY OF THE INVENTION

Utilized as part of a complete system of automated mail handling, the present invention overcomes the disadvantages of the prior art by providing an apparatus and method for accurately measuring the weight of vertically oriented mailpieces without stopping the mail handling process. In a currently preferred embodiment of the invention, a bottom belt transport oriented parallel to the base and with vertical baffles is mounted on a weighing mechanism (load cell) which in turn is mounted on the base of the apparatus. In this configuration, mailpieces enter the transport in a vertical orientation and are biased against the bottom of the belt by

gravity. This eliminates the need for ski rollers, which create vibrations, as they engage and disengage the mailpieces. Only two rotating elements are required in this transport, which also reduces vibration. By minimizing vibration, a measurement of the weight of the mailpieces can be determined more accurately and quickly, thereby increasing overall throughput of the apparatus.

In another currently preferred embodiment, a bottom belt transport, also oriented parallel to the base, is mounted on a pair of load cells which, in turn, are independently mounted to the base of the apparatus. Again, mailpieces enter the transport in a vertical orientation and are biased against the bottom of the belt by gravity. A first load cell is located at the input end of the apparatus, and a second load cell is located at the output end of the apparatus. The signals received from the first and second load cells are combined via a trim balance circuit which, in turn, transmits the weight to the main processing system of the mail handling system in which the inventive apparatus is installed.

In yet another preferred embodiment, the vertical baffles are held in place by baffle support brackets which, in turn, are mounted directly to the base of the apparatus. Isolating the baffles from the transport and load cells reduces vibration at the load cells by limiting the vibration caused by mailpieces impacting the baffles. By minimizing vibration, a measurement of the weight of the mailpieces can be determined more accurately and quickly, thereby increasing overall throughput of the apparatus. Vertical baffles held in place by baffle support brackets may be utilized in apparatus using either one or a plurality of load cells to measure the weight of the mailpiece in the transport.

In yet another preferred embodiment, the transport belts are oriented perpendicular to the base. The entire system is mounted on top of a structural pillar connected to the base, thus making the entire system suspended in air. A single load cell has its weighing surface oriented parallel to the transport belts, or perpendicular to the base. Any vibrations or oscillations in the

mechanics of the system would be minimized because they would not occur in the same vector as the weight of the mailpiece.

Thus, an advantage of the present invention is that it may accurately weigh mailpieces in a vertical orientation, or on their bottom edge. Another advantage is that the present invention
5 reduces the overall vibration present in the system, thereby providing a more accurate calculation of weight. Yet another advantage of the present invention is that it does not require the transport to be stopped in order to calculate the weight of a mailpiece.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of
10 the invention. The aforementioned advantages are illustrative of the advantages of the various embodiments of the present invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

15 The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate a presently preferred embodiment of the invention, and together with the general description given above and the detailed description of the preferred embodiment given below, serve to explain the principles of the invention.

20 Figure 1 is an isometric view of a dual load cell embodiment of the mail handling apparatus with a horizontal mail weighing transport of the present invention;

Figure 2 is a side view of the mail handling apparatus illustrated in Figure 1;

Figure 3 is an end view of the mail handling apparatus illustrated in Figure 1;

Figure 4 is a cross sectional end view of the mail handling apparatus illustrated in Figure 1;

Figure 5 is a circuit diagram of a trim balance circuit for use in a dual load cell embodiment of the mail handling apparatus of the present invention;

Figure 6 is an isometric view of a single load cell embodiment of the mail handling apparatus of the present invention with a horizontal mail weighing transport;

5 Figure 7 is a side view of the mail handling apparatus illustrated in Figure 6;

Figure 8 is a front view of a single load cell embodiment of the mail handling apparatus of the present invention with a vertical mail weighing transport; and

Figure 9 is a rear view of a single load cell embodiment of the mail handling apparatus illustrated in Figure 8;

10 Figure 10 is a flow diagram of the stop on demand weighing process.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Horizontal Mailpiece Weighing Transport with Dual Load Cells

Referring to Figures 1, 2, 3 and 4, a mailpiece weighing transport **102** is shown. Mailpiece weighing transport **102**, as will be discussed in more detail below, weighs and transports an individual mailpiece **104** along transport belt **106** from the input end of mailpiece weighing transport **102**, generally designated by arrow **108a** to the output end of mailpiece weighing transport **102**, generally designated by arrow **108b**. The course that the mailpiece **104** travels from the input end **108a** to **108b** is the transport path.

Mailpiece weighing transport **102** includes a base **110** upon which all of the components of mailpiece weighing transport **102** are mounted. In one preferred embodiment, a pair of load cells **112a** and **112b** are used to measure the weight of mailpiece **104** as it travels through mailpiece weighing transport **102**. Load cell **112b** is mounted on base **110** at input end **108b** and load cell **112a** is mounted on base **110** at output end **108a**. Load cell support brackets **114a** and **114b** connect load cells **112a** and **112b** to support plate **120**. Any type of forward driving mechanism can be used to transport mailpiece **104**. Preferably, the forward driving

mechanism comprises a transport belt **106**. Transport belt **106** is attached to support plate **120** by drive pulley **116** and idler pulley **118** and is supported by slider plate **122** which is also attached to support plate **120**. Locomotion to the system is provided by motor **130** which is mounted on mailpiece weighing transport **102** and directly connected to drive pulley **116**. Along the transport path are guides that ensure the mailpiece **104** stays on the transport path. Support baffles **124a** and **124b**, examples of guides, are mounted parallel to each other on opposing sides of transport belt **106**. Support baffle **124a** is held in place by support baffle brackets **126a**, **126b** and **126c** which are mounted on base **110**. Support baffle **124b** is held in place by support baffle brackets **126d**, **126e** and **126f** which are mounted on base **110**.

In general, the present invention determines the weight of a mailpiece **104** by measuring the load generated (the signal output by the load cells **112a** and **112b** combined) by a mailpiece **104** combined with the weighing platform (the components of mailpiece weighing transport **102** which are mounted on top of the load cells **112a** and **112b**), then subtracting the known load generated by the weighing platform (the tare). The remaining load is assumed to be generated by mailpiece **104** and any transient vibrations caused by the system and/or movement of mailpiece **104**. The measurement of the load minus the tare is then filtered to account for any transient vibrations, and the resulting measurement is then converted to a weight measurement and transmitted to mail processing system controller **100** (such as the WOW board utilized in Pitney Bowes Paragon® and Galaxy® automated mail processing systems). In a multiple load cell configuration, the measurements from each of the load cells **112a** and **112b** are combined using a trim balance circuit **128** before the measurement is transmitted for further processing to determine the weight of mailpiece **104**.

In operation, a mailpiece **104** enters the mailpiece weighing transport **102** in a vertical orientation at input end **108a** and travels along on transport belt **106** towards output end **108b**. Mailpiece **104** is biased against transport belt **106** by a normal force, gravity, and is maintained in a vertical orientation by support baffles **124a** and **124b** that prop up the side surface of the

mailpiece **104**. Support baffles **124a** and **124b** prevent mailpiece **104** from toppling over as it is moved through mailpiece weighing transport **102**. The weighing platform of mailpiece weighing transport **102** consists of transport belt **106** (an endless flat belt) supported between drive pulley **116** and idler pulley **118** with slider plate **122** which are mounted together to support plate **120**.

- 5 Forward motion is provided to transport belt **106** by motor **130** which is mounted on support plate **120** and directly connected to drive pulley **116**.

As mailpiece **104** moves along transport belt **106**, it causes load cells **112a** and **112b** to generate electrical analog output signals proportional to the force being applied to the top surface of the load cells **112a** and **112b** in response to the force of gravity acting upon the weighing platform and the mailpiece **104**. The electrical signals from **112a** and **112b** can be combined into a single signal via any appropriate signal converter known in the art. For example, the electrical signal can be combined via a trim balance circuit **128** and then transmitted to mail processing controller **100**.

Figure 5 is an illustration of the trim balance circuit **128**. The trim balance circuit is an example of a circuit that can be used in the mailpiece processing system. Any type of circuit that can combine the two input signals from the dual load cells **112a** and **112b** into a single output signal is appropriate for the system. The first connector **500** has eight terminals which represent +15 voltage DC power supply, positive side of the first signal from load cell **112a**, negative side of the first signal from load cell **112b**, ground, - 15 voltage DC power supply, positive side of the second signal from load cell **112b**, negative side of the second signal from load cell **112b** and ground. At nodes **502** and **504** are variable resistors **R1** and **R2** that can have a maximum resistance of about twenty ohms each. Between nodes **506** and **508** are two capacitors **C1**, **C2** in parallel. The second connector **510** has four terminals which represent +15 voltage DC power supply, positive side of output signal that proceeds to the mail processing controller **100**, negative side of output signal that also proceeds to the mail processing controller **100**, and ground.

Referring again to figures 1 through 4, support baffles **124a** and **124b**, which prevent mailpiece **104** from toppling over as it is conveyed through mailpiece weighing transport **102**, are mounted on support baffle brackets **126a**, **126b**, **126c**, **126d**, **126e**, and **126f** which are mounted to base **110**. Connecting the support baffles **124a** and **124b** in a vertical orientation to base **110** via on support baffle brackets **126a**, **126b**, **126c**, and **126d**, **126e**, **126f** reduces transient vibration at load cells **112a** and **112b** by isolating vibrations caused by mailpiece **104** impacting support baffles **124a** and **124b**. This arrangement also reduces the weight being carried by the load cells, in particular this configuration reduces the tare weight, thereby resulting in a more sensitive measurement of the load generated by mailpiece **104**.

Horizontal Mailpiece Weighing Transport with a Single Load Cell

Referring to Figures 6 and 7, a single load cell mailpiece weighing transport **640** is shown. Mailpiece weighing transport **640**, as will be discussed in more detail below, weighs and moves an individual mailpiece **641** along transport belt **642** from the input end of mailpiece weighing transport **640**, generally designated by arrow **644a** to the output end of mailpiece weighing transport **640**. The course that the mailpiece **641** travels from the input end **644a** to **644b** is the transport path.

Mailpiece weighing transport **640** includes a base **646** upon which all of the components of mailpiece weighing transport **640** are mounted. In one preferred embodiment, a single load cell **648** having a weighing surface **649** is used to measure the weight of a mailpiece **641** as it travels through mailpiece weighing transport **640**. Load cell **648** is mounted on base **646** at the center of gravity of mailpiece weighing transport **640**. Transport belt **642** is supported by drive pulley **652** and idler pulley **654** which, in turn, are connected to support plate **651**. Transport belt **642** is also supported by slider plate **650** which is also connected to support plate **651**. Locomotion to the system is provided by motor **630** which is mounted on mailpiece weighing transport **640** and directly connected to drive pulley **652**. Support baffles **656a** and **656b** are mounted parallel to each other and in a vertical orientation on opposing sides of transport belt

642. Support baffle **656a** is held in place by support baffle brackets **658a**, **658b** and **658c** which are mounted on slider plate **650**. Support baffle **656b** is held in place by support baffle brackets **658d**, **658e** and **658f** which are mounted to the support plate **651**.

In general, the single load cell embodiment of the invention functions the same as the dual load cell embodiment. The single load cell embodiment illustrated herein has the vertical support baffles integrated into the weighing platform as opposed to being attached to the base as illustrated in the dual load cell configuration. It will be understood by one skilled in the art that single and multiple load cell configurations may be provided with either base attached support baffles or weighing platform attached support baffles. It will also be understood that the single load cell embodiment does not require the use of a trim balance circuit to combine the load measurement prior to weight calculation. Just as with the dual load cell embodiment, the measurement of the load minus the tare is filtered to account for any transient vibrations and the resulting measurement is then converted to a weight measurement and transmitted to mail processing system controller **100** (such as the WOW board utilized in Pitney Bowes Paragon® and Galaxy® automated mail processing systems).

In operation, a mailpiece enters the mailpiece weighing transport **640** in a vertical orientation at input end **644a** and moves along on transport belt **642** towards output end **644b**. The mailpiece is biased against transport belt **642** by gravity and is maintained in a vertical orientation by support baffles **656a** and **656b** which prevent the mailpiece from toppling over as it is conveyed thorough mailpiece weighing transport **640**. The weighing platform of mailpiece weighing transport **640** consists of transport belt **642** (an endless flat belt) supported between drive pulley **652** and idler pulley **654** with slider plate **650** which are together mounted to support plate **651**, wherein forward motion is provided to transport belt **642** by motor which is mounted also on support plate **651** and directly connected to drive pulley **652**, and support baffles **656a** and **656b** are also part of the weighing platform.

Vertical Mailpiece Weighing Transport

The embodiments in Figures 1 through 7 feature a mail processing system with a mail weighing transport **102**, **640** that is horizontal (parallel) to the base **110**, **646**. In an alternative embodiment, the mail weighing transport can be constructed such that it is vertical (perpendicular) to the base.

Referring to Figures 8 and 9, a vertical mailpiece weighing transport **802** is shown. Mailpiece weighing transport **802** weighs and transports an individual mailpiece **804** along the transport path from the input end of the mailpiece weighing transport **802**, generally designated by arrow **808a** to the output end of the mailpiece weighing transport **802**, generally designated by arrow **808b**.

Mailpiece weighing transport **802** includes base **810** upon which all of the components of mailpiece weighing transport **802** are mounted. Structural pillar **812** has a top surface **814** and a back surface **816**. Structural pillar **812** is connected to base **810** and is responsible for suspending all of the components of the mailpiece weighing transport **802**. Single load cell **818** has a weighing surface **820** and is located on the top surface **814** of the structural pillar **812**.

Support plate **822** is a structure that holds all of the components of the mailpiece weighing transport **802** with the exception of base **810**, structural pillar **812**, and single load cell **818**. Support plate **822** has a front side **824**, back side **826**, input side **828**, output side **830**, and bottom edge **831**. The center of back side **826** of support plate **822** is connected to the center of the weighing surface **820** of single load cell **818**. Since single load cell **818** is connected to the center of the back side **826** of the support plate **822**, single load cell **818** is located at the center of gravity of the support plate **822** and the mailpiece weighing transport **802**. A drive pulley **832** and an idler pulley **834** are connected to the output side **830** and input side **828** of support plate **822**, respectively. A plurality of transport belts **836** having a front side **838** and back side **826** are connected to support plate **822** by drive pulley **832** and idler pulley **834** (both pulleys are depicted by phantom lines in Figure 9). Both the front side **838** and back

side **840** of the plurality of transport belts **836** reside in planes that are perpendicular to base **810**. Suspended pillar **842** having a front side **846** and back side **848**, is mounted to back side **840** of support plate **822**. A motor **850** is electrically connected to the drive pulley **832** and physically connected to the back side **848** of suspended pillar **842**. Transport guide **852**, having
5 mounting points **P1** and **P2**, is mounted to bottom edge **831** of support plate **822**. Transport guide **852** is parallel to base **810** and runs the entire length of bottom edge **831** of support plate **822**. Holding brackets **854**, **856** are mounted to mounting points **P1** and **P2** by C-clamps **858**, **860**. Alternatively, the C-clamps **858**, **860** can be eliminated, and the holding brackets **854**, **856** can be directly mounted to transport guide **852**. Mounted to holding brackets **854**, **856** are flat
10 springs **862**, **864**. A first sensor **866** is connected to the base on the input side. A second sensor **868** is connected to the base on the output side. Any type of sensor that can detect the movement of a mailpiece in the mail weighing system can be used. For example, optical sensors are able to perform this function.

A mailpiece **804** in a vertical orientation enters the vertical mail weighing transport **802** at
15 the input end **808b**. Mailpiece **804** is initially biased against front side **838** of transport belts **836**. As the mailpiece **804** moves along the mail weighing system **802**, the bottom edge of the mailpiece is in contact with transport guide **852**. The mailpiece **804** is kept in contact with front side **838** of transport belts **836** by the normal force created by flat springs **858**, **860**. In this
vertical mail weighing system **802**, the weighing platform comprises all of the components
20 attached to single load cell **818**, that is support plate **822**, pulleys **832**, **834**, transport belts **836**, holding brackets **854**, **856**, C-clamps **858**, **860**, flat springs **862**, **864**, transport guide **852**, suspended pillar **842**, and motor **850**. The entire weighing platform constitutes the tare. The weight of mailpiece **804** is determined by measuring the load generated (the signal output by single load cell **818**) when the mailpiece **804** pushes against the weighing surface **820** of the
25 single load cell **818** minus the tare. As with the previous embodiments, the remaining load is

assumed to be generated by mailpiece **804**, and the signal produced by single load cell **818** is converted to a weight measurement and transmitted to mail processing system controller **100**.

The advantage of the vertical configuration of the mail weighing transport **802** is that it minimizes the introduction of vibrations or oscillations as noise into the weighing system. For example, pulleys **832**, **834** and transport belts **836** have the potential to produce vibration which would impact the weighing process. By having the weighing surface of the load cell oriented vertically, any vibrations caused by pulleys **832**, **834** and transport belts **836** are further minimized since some of the vibrations are divided between vertical and horizontal vectors. In contrast, the entire vibration would be experienced by the load cells in a horizontal mail processing system.

In any of the aforementioned embodiments of the present invention, a stop on demand feature can be added to the mail processing system. Whenever any parameter is measured, there is an inherent error associated with the measurement, the margin of error. Errors can arise from the transitory oscillations or vibrations of the mailpiece weighing transport. In the case of the present invention, an error is always associated with the measured weight of the mailpiece. If a weight break falls within a measurement plus or minus the margin of error, then the mailpiece should be reweighed to verify the measurement. For example, the U.S. Postal Service determines the proper postage for a mailpiece based on weight in one ounce increments, or weight breaks. A first class letter weighing one ounce or less requires thirty-four cents postage. If a letter weighs more than one ounce (approximately twenty-eight grams), then the postage increases to fifty-five cents. Thus it is critical for the weights to be accurately measured when the measured weights fall within the margin of error of the system. This problem solved in three ways. The first is to apply more postage than necessary. This method is not optimal because it results in added unnecessary expense. The second way is to divert the mailpiece down a separate path and have the mailpiece reweighed by hand or a more sensitive system. The third way is to stop the transport and allow the load cell to stabilize. After

stabilization, the mailpiece can be reweighed. To capture this criticality, a stop on demand algorithm can be implemented in the mail processing system controller **100**.

Referring to Figure 10, at step **1000**, the mailpiece weighing transport is initiated. At step **1020**, a decision is made as to whether the first sensor **866** is blocked by mailpiece **804**. If the first sensor **866** is blocked, then mailpiece **804** may need to be removed from the mailpiece weighing transport. If not, mailpiece **804** proceeds to the load cell and the weighing begins, step **1030**. After weighing, the mailpiece **804** progresses along the transport path. At step **1040**, a decision is made as to whether the second sensor **868** is blocked by mailpiece **804**. If so, the mailpiece may not be removed. If not, the stop-on-demand system progresses to step **1050**. At this step, a decision is made as to whether the weight obtained was satisfactory. An unsatisfactory weight, for example, would be one that has a postal weight break within the margin of error of the weight obtained. If an unsatisfactory weight is obtained, the transport is stopped in step **1060**. Then, the weighing is continued at step **1070**. Continued weighing can include the reweighing of mailpiece **804**. Step **1080** allows for a loop that keeps reweighing mailpiece **804** until a satisfactory weight is obtained. Only when a satisfactory weight is obtained does mailpiece **804** proceed to step **1090** in which the mailpiece weighing transport **802** is restarted.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details, and representative devices, shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims. For example while the preferred embodiment is described in connection with a mail handling machine, any apparatus for handling articles can utilize the principles of the invention. Additionally, while a mailpiece weighing transport utilizing belts is described it is known to use rollers and other transport mechanisms.